

ALUMA TOWER CARGO TRAILER SPEC SHEET

TRAILER MODEL	ECT-16 EB4	ECT-20 EB4	ECT-20D4 EB4	ECT-24D4 EB4
TOWER AVAILABLE WITH TRAILER UNIT	35', 40', 50', 60'	35', 40', 50', 60', 75', 100'	35', 40', 50', 60'	35', 40', 50', 60', 75', 100'
ENCLOSURE SIZE	204" L x 96" W x 78" H	252" L x 96" W x 75" H	204" L x 96" W x 78" H	240" L x 96" W x 75" H
TRAILER WIDTH OVERALL	102"	102"	102"	102"
ENCLOSURE INTERIOR HEIGHT	78"	75"	78"	75"
TRAILER LENGTH O'ALL (W/O COUPLER)	21' (252")	24' (288")	24' (288")	28' (336")
TRAILER GROSS VEHICLE WGHT (GVWR)	6,990 LBS	9,990 LBS	9,990 LBS	9,990 LBS
TRAILER GROSS AXLE WGHT (GAWR)	3,500 LBS	5,200 LBS	5,200 LBS	5,200 LBS
TRAILER APPROX. WEIGHT SHIPPED (VARIES WITH DIFFERENT ACCESSORIES)	3,500 LBS	4,400 LBS	4,800 LBS	5,300 LBS
NUMBER OF AXLES	2 (TANDEM)	2 (TANDEM)	2 (TANDEM)	2 (TANDEM)
AXLE CAPACITY RATING (EACH)	3,500 LB	5,200 LB	5,200 LB	5,200 LB
STANDARD COUPLER SIZE	2 5/16" BALL	2 5/16" BALL	2 5/16" BALL	2 5/16" BALL
ELECTRIC BRAKES	4 WHEEL ELECTRIC BRAKES	4 WHEEL ELECTRIC BRAKES	4 WHEEL ELECTRIC BRAKES	4 WHEEL ELECTRIC BRAKES
TIRE SIZE (NOTE: ALL RADIAL TIRES!)	ST205/75R/15	ST225/75R/15	ST225/75R/15	ST225/75R/15
TIRE LOAD RANGE	C	D	D	D
TIRE CAPACITY AND LOAD RATE	1,760 LB	2,540 LB	2,540 LB	2,540 LB
TIRE P.S.I.	50 PSI	65 PSI	65 PSI	65 PSI
WHEEL / RIM SIZE (DIA./WIDTH/BOLT PATTERN)	15" / 6" / 6 ON 5.5"	15" / 6" / 8 ON 6.5"	15" / 6" / 8 ON 6.5"	15" / 6" / 8 ON 6.5"