

SPECIFICATIONS	ECT-16
TOWER AVAILABLE WITH UNIT	35FT, 40FT, 50FT, 60FT
ENCLOSED SIZE	204IN L x 96IN W x 78IN H
TRAILER WIDTH OVERALL	102IN
ENCLOSURE INTERIOR HEIGHT	79 IN
TRAILER LENGTH OVERALL (W/O COUPLER)	21FT (252IN)
TRAILER GROSS VEHICLE WEIGHT (GCWR)	6,990 LBS
TRAILER GROSS AXLE WEIGHT (GAWR)	3,500 LBS
TRAILER <i>APPROXIMATE</i> SHIPPING WEIGHT (<i>VARIES W/ DIFFERENT ACCESSORIES</i>)	3,500 LBS
NUMBER OF AXLES	2 (TANDEM)
AXLES CAPACITY RATING (EACH)	3,500 LB
STANDARD COUPLER SIZE	2 5/16IN BALL
BREAKS	4 WHEEL ELECTRIC BRAKES
TIRE SIZE (<i>ALL RADIAL TIRES</i>)	ST205/75R/15
TIRE LOAD RANGE	C
TIRE CAPACITY AND LOAD RATE	1,760 LB
TIRE P.S.I.	50 PSI
WHEEL / RIM SIZE (DIA./WIDTH/BOLT PATTERN)	15IN / 6IN / 6 ON 5.5IN
UID LABEL MIL-STD-130	YES

- ACCESSORIES AVAILABLE**
- Guy Kit Assembly
 - Anchor Kit
 - Dual Obstruction Light
 - Antenna Stand-off
 - 12V DC Electric Winch
 - Electric Winch for tilting Tower 12V DC
 - 12V DC Battery Pack
 - All Aluminum Storage Box
 - Spare Tire
 - A/C and Heat (Roof or Wall Mounted)
 - 12V Work Lights
 - 120V 500 Watt Floodlight With 5FT Telescoping Pole
 - 120V 500 Watt Removable Floodlight w/ Tripod Base & 50FT Cord
 - All Aluminum Co-Ax Cable Reel
 - I/O Port Rostac
 - Telephone Inlet
 - Dual Cat5
 - 20 Amp Twist Lock
 - 5Kw to 20Kw Diesel Quiet Run Gen.
 - Custom All Aluminum Fuel Tank (25 Gal. to 150 Gal.)
 - Electronic Equipment Rack
 - Complete Grounding System
 - Automatic & Manual Transfer Switch
 - Shore-Power Cord w/ Twist Lock Connection
 - Dri-Deck Flooring
 - AB Aluminum Work Station Cabinets
 - Bunk Bed
 - Roof Access Ladder
 - Electric Tongue Jack
 - Exterior GFI Receptacle
 - Solar Battery Charge
 - Aluminum Underbody Dual Battery Box w/ Slide out Tray
 - Cable Ring
 - 22FT Little Giant Ladder
 - Interior Co-Ax Cable Tray.



Not drawn to scale.

Aluma Tower Company, Inc. reserves the right to make changes at any time to information contained in this document.