


SPECIFICATIONS	TM 51-35
TOWERS AVAILABLE WITH UNIT	T-50XHD, T-50XXHD, T-75XHD, T-100H
TRAILER WIDTH OVERALL	89 1/2IN
TRAILER WIDTH, FRAME ONLY	66IN
TRAILER DECK HEIGHT	23IN
TRAILER LENGTH OFTALL (W/O COUPLER)	21FT10IN (263IN)
TRAILER GROSS VEHICLE WGHT (GVWR)	6,990 LBS
TRAILER BARE WEIGHT	1800 LBS
TRAILER GROSS AXLE WGHT (GAWR)	3,500 LBS
TRAILER APPROX. WEIGHT SHIPPED (VARIES WITH DIFFERENT ACCESSORIES)	2,400 LBS
NUMBER OF AXLES	2 (TANDEM)
AXLE CAPACITY RATING (EACH)	3500 LB
COUPLER CHANNEL (POSITIONS/HOLES)	5 POS./6 HOLES
STANDARD COUPLER SIZE	2 5/16IN BALL, 7,000 LB CAP., 2 HOLES
ELECTRIC BRAKES	4 WHEEL ELECTRIC BRAKES
TIRE SIZE (NOTE: ALL RADIAL TIRES!)	ST205/75R/14
TIRE LOAD RANGE	C
TIRE CAPACITY AND LOAD RATE	1760 LB
TIRE P.S.I.	50 PSI
WHEEL / RIM SIZE (DIA./WIDTH/BOLT PATTERN)	14IN / 6IN / 5 ON 4.5IN
FINISHED HEIGHT, TOWER IN USAGE POSITION	119IN
FINISHED HEIGHT, TOWER IN STOWED POSITION	95IN
OVERALL LENGTH WITH TOWER MOUNTED	26FT (312IN)
UID Label MIL-STD-130	Yes

ACCESSORIES AVAILABLE
Guy Kit Assembly
Anchor Kit
Antenna Stand-off
12V DC Electric Winch
Electric Winch for tilting Tower 12V DC
12V DC Battery Pack
All Aluminum Storage Box
Spare Tire
12V Work Lights
120V 500 Watt Removable Floodlight w/ Tripod Base & 50FT Cord
All Aluminum Co-Ax Cable Reel
I/O Port Rostec
5Kw to 15Kw Diesel Quiet Run Gen.
Custom All Aluminum Fuel Tank (25 Gal. to 150 Gal.)
Outdoor Radio Equipment Cabinet
Complete Grounding System
Manual Transfer Switch
Automatic Transfer
Shore-Power Cord w/ twist Lock Connection
Electric Tongue Jack
Exterior GFI Receptacle
Cable Ring Assembly
22FT Little Giant Ladder



Not drawn to scale.

Aluma Tower Company, Inc. reserves the right to make changes at any time to information contained in this document.